Anti-Slip Pearls

HEMPEL

0049(0)40-8890100 www.toplicht.de





Product Data Hempel's Anti-Slip Pearls 69070



Description:	HEMPEL'S ANTI-SLIP PEARLS 69070 can be added to all types of paint where a non-slip surface is required.
Recommended use:	Mix with Hempel's topcoats and varnishes to obtain non-slip finishes on decks other surfaces.
Availability:	Part of European Yacht assortment. Local availability subject to confirmation.
PHYSICAL CONSTANTS:	
Shade nos/Colours:	10000/ White.
Flash point:	None.
Specific gravity:	1 kg/litre [7.9 lbs/US gallon]
VOC content:	0 g/l [0 lbs/US gallon] The physical constants stated are nominal data according to the HEMPEL Group's approved formulas.
APPLICATION DETAILS:	
Application method:	Roller
Safety:	Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Safety Data Sheets and follow all local or national safety regulations.

Anti-Slip Pearls

0049 (0)40-8890 100 www.toplicht.de

Product Data Hempel's Anti-Slip Pearls 69070



TOPLICHT

Notkestraße 97 · 22607 Hamburg

REMARKS:		
Application(s):	Stir ANTI-SLIP PEARLS thoroughly into the paint until a uniform mixture has been obtained ANTI-SLIP PEARLS for 3/4 I of paint. Usually one coat is sufficient but if a more coarse structure required, apply one more coat.	
Overcoating:	If the maximum overcoating interval is exceeded, clean with fresh water and allow to dry. Li and remove all dust prior to repainting. If surface has been contaminated by oils and pollutants, thoroughly remove with suitable de rinse with fresh water and allow to dry. Light abrade and remove all dust prior to repainting.	etergent,
Note:	HEMPEL'S ANTI SLIP PEARLS 69070	
ISSUED BY:	HEMPEL A/S	6907010000