Product Safety Data Sheet	Document No.		1
	Issue	01.00	
	Date Last Amended	July 2022	
	Last Amended by	MLN	ocean
Document Title	LB14E Lithium Battery Module PSDS		SIGNAL

Product Name:	SafeSea Lithiu	m Battery Module		Type Nº:	LB14E
For use with:	EPIRB Models: Pro, rescueME		Pro, rescue	eME EPIRB3, SafeSea	EPIRB2
Chemistry:	LiFeS ₂	Total Weight:	103g	Nominal Voltage:	3V
Construction:				batteries, each of two tal 6 cells in series.	
Lithium weight	/ cell: 0.98	g Total I	ithium w	eight/battery:	1.96g

Section 1 – Manufacturer Information

Manufactured by:Ocean Signal Ltd., Unit 4, Ocivan Way, Margate, Kent, CT94NN, United Kingdom

Telephone number: +44 (0)1843 282930

Section 2 – Hazards Identification

This battery module is a sealed unit. In this condition there are no hazards identified. Should the battery be damaged to cause leakage of the cell contents, the following hazards should be noted.

Ingestion: Swallowing the contents of a damaged battery can be harmful

Inhalation: Contents of a damaged battery can cause respiratory irritation

Skin Contact: Contents of a damaged battery can cause irritation

Eye Contact: Contents of an damaged battery can cause severe irritation

Section 3 – Ingredients

Important Note: This battery module should not be opened or burned. Exposure to the contents may be harmful.

Material or Ingredient	PEL (OSHA)	TLV (ACGIH)	%/wt.
Lithium (CAS# 7439-93-2)	None Established	None established	6.3-6.6
Lithium Iodide (CAS# 10377-51-2)	None Established	None Established	0.3-3
Iron Disulfide (CAS# 1309-36-0)	None Established	None Established	28-38
1,2-Dimethoxyethane (CAS# 110-71-4)	None Established	None Established	2-4
1,3-Dioxolane (CAS# 646-06-0)	None Established	20 ppm TWA	5-9
Carbon Black (CAS# 1333-86-4)	3.5mg/m ³ TWA	3.5mg/m ³ TWA	0-4
Graphite (CAS# 7782-42-5)	15mg/m ³ TWA (total dust) 5mg/m ³ TWA (respirable fraction)	2mg/m ³ TWA (respirable fraction	0-4

Product Safety Data Sheet	Document No.		
	Issue	01.00	
	Date Last Amended	July 2022	
	Last Amended by	MLN	ocean
Document Title	LB14E Lithium Battery Module PSDS		SIGNAL

Material or Ingredient	PEL (OSHA)	TLV (ACGIH)	%/wt.
Non Hazardous Components			
Steel (CAS#7439-89-6)	None Established	None Established	18-22
Plastic and other	None Established	None Established	Remainder

Section 4 –	Section 4 – First Aid Measures		
Ingestion:	Seek medical advice. Do not induce vomiting or give food or drink.		
Inhalation:	Seek medical attention. Provide fresh air		
Skin Contact:	Remove any contaminated clothing and wash affected areas with soap and water.		
Eye Contact:	Seek medical attention. Immediately flush eyes with water for a minimum of 15minutes. Ensure that both upper and lower eyelids are lifted during the flushing process.		

Section 5 – Fire Fighting Measures

In case of fire involving lithium batteries, flood the area with water or smother with a class D fire extinguishing material suitable for lithium metal. (e.g. Lith-X)

Note: Water may not completely extinguish burning lithium batteries but will keep adjacent batteries cool reducing the risk of the fire spreading. As burning batteries will burn themselves out, flooding with water will control virtually all fires involving lithium batteries. However, the contents of lithium batteries will react with water to release hydrogen gas. In enclosed spaces this can cause an explosive mixture. Use a smothering agent in enclosed spaces which will extinguish burning lithium batteries.

Fire responders should wear self contained breathing apparatus. Burning lithium-Iron disulfide batteries produce toxic and corrosive lithium hydroxide fumes and sulphur dioxide gas.

Section 6 - Accidental Release Measures

Should batteries leak the following actions are recommended:

Ventilation:	Keep room containing leaking lithium batteries well ventilated
Respiratory Protection:	Avoid exposure to fumes from open or leaking batteries
Eye protection:	Wear safety glasses with side shields when handling leaking batteries
Gloves:	Neoprene or natural rubber gloves should be worn when handling leaking batteries
Storage:	Leaking batteries should be stored in a leak proof container

Section 7 – Handling and Storage

Storage: Store in a cool, well ventilated area. Elevated temperature may result in shortened battery life.

Document Title	LB14E Lithium Battery Module PSDS		SIGNAL
	Last Amended by	MLN	ocean
Product Safety Data Sheet	Date Last Amended	July 2022	
	Issue	01.00	
	Document No.		

Handling:	Avoid accidentally short-circuiting batteries. Prolonged short-circuiting can cause the battery temperature to rise and significantly reduce
Charging	battery life.
Charainai	These batteries are not decigned for charging the net attempt to

Charging: These batteries are not designed for charging. Do not attempt to recharge the battery. Recharging may result in cell venting or rupture.

Section 8 – Exposure Controls / Personal Protection

No special requirements are required for this battery under normal circumstances.

Section 9 – Physical and Chemical Properties			
Boiling Point at 760mm Hg (°C)	Not applicable for this item		
Vapour Pressure (mm Hg at 25°C)	Not applicable for this item		
Vapour Density	Not applicable for this item		
Density (g/cm ³)	1.7-2.0		
Percent volatile by volume (%)	Not applicable for this item		
Evaporation Rate	Not applicable for this item		
Physical State	Solid		
Solubility in water	Not applicable for this item		
pH	Not applicable for this item		
Appearance and odour	Solid object / no odour		

Section 10 – Stability and Reactivity

No stability or reactivity issues identified

Section 11 – Toxicological Information

This battery module is not classified as hazardous waste. This battery module has been manufactured in accordance with the EU ROHS directive, 2011/65/EU.

Section 12 – Ecological Information

No ecological issues have been identified for this battery

Section 13 – Disposal Considerations

Dispose of battery module in accordance with applicable local regulations

Section 14 – Transport Information

This battery module has been tested in accordance with subsection 38.3 of part III of the UN Manual of Tests and Criteria. Summary test reports are available from Ocean Signal on request.

This battery module should be transported by air in accordance with the IATA dangerous goods regulations 63rd edition, class 9, UN3090, proper name "Lithium metal batteries" and packed according to packing instruction 968 section IB.

	Document No.		
Product Safety Data Sheet	Issue	01.00	
	Date Last Amended	July 2022	
	Last Amended by	MLN	ocean
Document Title	LB14E Lithium Battery Module PSDS		SIGNAL

When supplied with equipment it is class 9, UN3091, proper name "Lithium metal batteries packed with equipment" and should be packed in accordance with packing instruction 969 section II.

The LB14E battery can be carried as personal luggage with the EPIRB on board aircraft under the conditions of clause 2.3.5.9 of the IATA dangerous goods regulations.

The battery modules may be transported by road under special provision 188 of the ADR.

Section 15 Regulatory Information

No additional regulatory requirements are identified for this battery module.

Section 16 – Other

No information